

# v1.20\_

SMG-, /etc/eltex-ngw/application.conf, **call outgoing.config, smg.conf.**

## /etc/eltex-ngw/application.conf

```
call {
    // Incoming (user to service) call config
    incoming.config = ""
    // Outgoing (service to user) call config
    outgoing.config = "smg.conf"
}
```

smg.conf ( /etc/eltex-ngw/gateway.d/) SMG-.

## /etc/eltex-ngw/gateway.d/smg.conf

```
// SMG host, port and RADIUS secret
connection {
    host = 192.168.23.175
    port = 3799
    secret = ngw
}

// NGW port and RADIUS secret
listen {
    port = 1814
    secret = ngw
}
```

### connection:

```
host = smg ;
port = smg ;
secret = RADIUS-Authorization smg .
```

### listen:

```
port = , NGW. , smg ;
secret = RADIUS-Accounting.
```

, eltex-ngw

```
root@vagrant-ubuntu18-bionic-64-SWLc:~# service eltex-ngw restart
```

SMG radclient CoA .

```
root@vagrant-ubuntu18-bionic-64-SWLC:~# echo Called-Station-Id="79964567890" | radclient -sx 192.168.1.10:  
3799 coa radiuspass  
Sending CoA-Request of id 150 to 192.168.1.10 port 3799  
    Called-Station-Id = "79964567890"  
rad_recv: CoA-ACK packet from host 192.168.1.10 port 3799, id=150, length=33  
    Calling-Station-Id = "73830012345"  
  
        Total approved auths: 1  
        Total denied auths: 0  
        Total lost auths: 0
```

CoA-ACK Calling-Station-Id .