

SSH, Telnet

- ip ftp client password
- ip ftp client username
- ip ftp source-ip
- ip sftp client password
- ip sftp client username
- ip ssh authentication algorithm disable
- ip ssh authentication retries
- ip ssh authentication timeout
- ip ssh client password
- ip ssh client source-ip
- ip ssh client username
- ip ssh dscp
- ip ssh encryption algorithm disable
- ip ssh host-key algorithm
- ip ssh key-exchange algorithm disable
- ip ssh key-exchange time
- ip ssh key-exchange volume
- ip ssh port
- ip ssh server
- ip telnet dscp
- ip telnet port
- ip telnet server
- show crypto key mypubkey
- update ssh-host-key

ip ftp client password

FTP.

(no) .

```
ip ftp client password { <CLEAR-TEXT> | encrypted <ENCRYPTED-TEXT> }
```

```
[no] ftp client password
```

<CLEAR-TEXT> – , [1 .. 16], [0-9a-fA-F];

<ENCRYPTED-TEXT> – , [2..32].

15

CONFIG

```
esr(config)# ip ftp client password test
```

ip ftp client username

FTP.

(no) .

```
ip ftp client username <NAME>
```

```
no ftp client username
```

<NAME> – , 31 .

15

CONFIG

```
esr(config)# ip ftp client username test
```

ip ftp source-ip

, FTP-.

(no) .

ip ftp source-ip <ADDR>

[no] ip ftp source-ip

<ADDR> – IP-, AAA.BBB.CCC.DDD, [0..255]

IP- , FTP-.

10

CONFIG

```
esr(config)# ip ftp source-ip 192.168.1.57
```

ip sftp client password

SFTP.

(no) SFTP.

```
ip sftp client password { <TEXT> | encrypted < ENCRYPTED-TEXT > }  
no ip sftp client password
```

<TEXT> – [1..16] ASCII-;

<ENCRYPTED-TEXT> – , [8..16] , [16..32]

15

CONFIG

```
esr(config)# ip sftp client password 123456789
```

ip sftp client username

SFTP.

(no) SFTP.

```
ip sftp client username <USERNAME>
```

```
no ip sftp client username
```

```
<USERNAME> - , 31 .
```

15

CONFIG

```
esr(config)# ip sftp client username esruser
```

ip ssh authentication algorithm disable

SSH-.

(no) SSH-.

```
[no] ip ssh authentication algorithm <ALGORITHM> disable
```

```
<ALGORITHM> - , [md5, md5-96, sha1, sha1-96, sha2-256, sha2-512, ripemd160].
```

15

CONFIG

```
esr(config)# no ip ssh authentication algorithm md5 disable
```

ip ssh authentication retries

SSH-.

(no) SSH- .

```
ip ssh authentication retries <NUM>
```

```
no ip ssh authentication retries
```

<NUM> – SSH- [1..10].

10

6

CONFIG

```
esr(config)# ip ssh authentication retries 5
```

ip ssh authentication timeout

, ssh- , SSH-.

(no) SSH- .

```
ip ssh authentication timeout <SEC>
```

```
no ip ssh authentication timeout
```

<SEC> – , [30..360].

10

120

CONFIG

```
esr(config)# ip ssh authentication timeout 60
```

ip ssh client password

SCP.

(no) .

```
ip ssh client password { <CLEAR-TEXT> | encrypted <ENCRYPTED-TEXT> }
no ssh client password
```

```
<CLEAR-TEXT> - , [1 .. 16] , [0-9a-fA-F];
<ENCRYPTED-TEXT> - , [2..32].
```

15

CONFIG

```
esr(config)# ip ssh client password test132
```

ip ssh client source-ip

IP- , SSH- .

(no) .

```
ip ssh client source-ip <ADDR>
no ssh client source-ip
```

```
<ADDR> - IP-, AAA.BBB.CCC.DDD, [0..255]. IP- -/ .
```

10

CONFIG

```
esr(config)# ip ssh client source-ip 192.168.22.78
```

ip ssh client username

SCP.

(no) .

```
ip ssh client username <NAME>
no ssh client username
```

<NAME> – , 31 .

15

CONFIG

```
esr(config)# ip ssh client username tester
```

ip ssh dscp

```
DSCP IP- SSH-.
(no) DSCP .
```

```
ip ssh dscp <DSCP>
no ip ssh dscp
```

<DSCP> – DSCP, [0..63].

32

10

CONFIG

```
esr(config)# ip ssh dscp 40
```

ip ssh encryption algorithm disable

```
SSH-.
(no) SSH-.
```

```
[no] ip ssh encryption algorithm <ALGORITHM> disable
```

<ALGORITHM> – , [aes128, aes192, aes256, aes128ctr, aes192ctr, aes256ctr, arcfour, arcfour128, arcfour256, blowfish, cast128, 3des].

CONFIG

```
esr(config)# ip ssh encryption algorithm aes128 disable
```

ip ssh host-key algorithm

Host-Key SSH-.

(no) Host-Key SSH-.

[no] ip ssh host-key algorithm <ALGORITHM> disable

<ALGORITHM> – , [dsa, ecdsa256, ecdsa384, ecdsa521, ed25519, rsa].

CONFIG

```
esr(config)# ip ssh host-key algorithm dsa disable
```

ip ssh key-exchange algorithm disable

SSH-.

(no) SSH-.

[no] ip ssh key-exchange algorithm <ALGORITHM> disable

<ALGORITHM> – , [dh-group1-sha1, dh-group14-sha1, dh-group-exchange-sha1, dh-group-exchange-sha256, ecdh-sha2-nistp256, ecdh-sha2-nistp384, ecdh-sha2-nistp521].

CONFIG

```
esr(config)# ip ssh key-exchange algorithm dh-group-exchange-sha1 disable
```

ip ssh key-exchange time

SSH-.

(no) SSH- .

```
ip ssh key-exchange time <SEC>
```

```
no ip ssh key-exchange time
```

<SEC>- , [1..72].

15

1

CONFIG

```
esr(config)# ip ssh key-exchange time 24
```

ip ssh key-exchange volume

, SSH-.

(no) , SSH- .

```
ip ssh key-exchange volume <DATA>
```

```
no ip ssh key-exchange volume
```

<DATA>- , [1..4096].

15

1000

CONFIG

```
esr(config)# ip ssh key-exchange volume 512
```

ip ssh port

SSH- .

(no) .

```
ip ssh port <PORT>
```

```
no ip ssh port
```

<PORT> – , [1..65535].

22

15

CONFIG

```
esr(config)# ip ssh port 3001
```

ip ssh server

SSH- .

(no) SSH-.

```
[no] ip ssh server [ vrf <VRF>]
```

<VRF> – VRF, 31, SSH-.

SSH- .

10

CONFIG

```
esr(config)# no ip ssh server
```

ip telnet dscp

DSCP IP- Telnet-.

(no) DSCP .

```
ip telnet dscp <DSCP>
no ip telnet dscp
```

<DSCP> – DSCP, [0..63].

32

15

CONFIG

```
esr(config)# ip telnet dscp 40
```

ip telnet port

Telnet- .

(no) .

```
ip telnet port <PORT>
no ip telnet port
```

<PORT> – , [1..65535].

23

15

CONFIG

```
esr(config)# ip telnet port 2001
```

ip telnet server

Telnet- .

(no) Telnet-.

```
[no] ip telnet server [vrf <VRF>]
```

<VRF>- VRF, 31 , Telnet-.

Telnet- .

15

CONFIG

```
esr(config)# no ip telnet server
```

show crypto key mypubkey

, SSH.

```
show crypto key mypubkey <OPTIONS>
```

<OPTIONS>- :

- dsa – DSA;
- ecdsa – ECDSA. , 256, 384 521;
- ed25519 – ED25519;
- rsa – RSA;
- rsa1 – RSA1.

15

ROOT

```
esr# show crypto key mypubkey rsa
Key data
-----
ssh-rsa
AAAAB3NzaC1yc2EAAAQABADQz750sWCQrnNufg1yhuksTFYCYdEf
gJZ9tWUvcssAZhCJWMewprXBuZMABzFmfBg157pgapxn2qJXJ8ESMV7X7gPfy
xQQah61376z3SFcpKvwudNgwHiS5HCYPRQWx2Xdaz/nJtYr5NpYgLPba68NC
iXcqEp7EPR5GojDVxpuDuk0hPFCihzmt5Yx8ZptJRzRtsuDQYlowv0Qa24kd
O1Q90/1qKfbAhB6XI601+dK5Vbj7giBESarcRn69/e/YVbdGBdT
E93QWFPKI
bm63imfbxRwWtcwsFdIH18Blv9ZqDqqF/IO3TkIKa31hV9Gnsaw1AXi/IdyY
bYPboHRdcTlH/ root@esr-1000
```

update ssh-host-key

SSH.

```
update ssh-host-key { dsa | ecdsa <ESCDAs> | ed25519 <ED25519> | rsa <RSA> }
```

dsa – DSA;
ecdsa – ECDSA;
• <ECDSA> – , 256, 384 521;
• , 521.
ed25519 – ED25519;
• <ED25519> – , [256..2048];
• , 2048.
rsa – RSA ;
• <RSA> – , [1024..2048];
• , 2048.

15

ROOT

```
esr(config)# update ssh-host-key ecdsa
```