

[NTU-RG-5XXX] MU MIMO

MU MIMO (Multiple User – Multiple Input Multiple Output) - , , .

MIMO , (.. ,) , , .

MU MIMO:

- 1. 802.11ac ax.
- 2. .

NTU WEB- NTU, Wireless/WLAN1(5Ghz)/Advanced Settings, «Enable MU MIMO» (Disabled) «Apply Changes».



NTU-RG-5440G-WZ:rev.B

Status	LAN	WiFi	WAN	Services	Advance	Diagnostics	Administration	Statistics
--------	-----	------	-----	----------	---------	-------------	----------------	------------

WLAN0 (2.4GHz) >
WLAN1 (5GHz) v
Status
Basic Settings
Advance Settings
Security Settings
Access Control
Wi-Fi Radar
WPS
EasyMesh >
Wi-Fi Isolation

WLAN Advanced Settings

Fragment Threshold:	2346 (256-2346)
RTS Threshold:	2347 (0-2347)
Beacon Interval:	100 (20-1024 ms)
Data Rate:	Auto
Preamble Type:	☒ Long Preamble ☐ Short Preamble
Client Isolation:	☐ Enabled ☒ Disabled
Protection:	☐ Enabled ☒ Disabled
Aggregation:	☒ Enabled ☐ Disabled
Short GI:	☒ Enabled ☐ Disabled
TX beamforming:	☒ Enabled ☐ Disabled
MU MIMO:	☐ Enabled ☒ Disabled
Multicast to Unicast:	☒ Enabled ☐ Disabled
Band Steering:	☐ Enabled ☒ Disabled Prefer 5GHz
WMM Support:	☒ Enabled ☐ Disabled
802.11k Support:	☒ Enabled ☐ Disabled