

## v1.14\_

### OID : 1.3.6.1.4.1.35265.1.60.1.1.1.2

: AA:BB:CC:DD:FF:00 wlan0, SSID 'test\_SSID', RSSI -79  
• (, , ).  
SSID .  
C : '79234567890' (AA:BB:CC:DD:FF:00) wlan1, SSID 'test\_hotspot\_SSID', Domain 'guest.test.root', RSSI -79  
SSID , . () .  
C : 'tester' (AA:BB:CC:DD:FF:00) wlan1, SSID 'test\_enterprise\_SSID', Domain 'enterprise.test.root', RSSI -79  
WPA-enterprise.

### OID : 1.3.6.1.4.1.35265.1.60.1.1.1.3

: AA:BB:CC:DD:FF:00 wlan0, SSID 'test\_SSID', RSSI -61, 'Sending station is leaving IBSS or ESS'  
: AA:BB:CC:DD:FF:00 wlan1vap1, SSID 'test\_enterprise\_SSID', RSSI -43, 'Sending station is leaving BSS'  
SSID WPA-enterprise Response Identify ( , .., MAC ) , , Failure Radius . DeAssoc 'Sending station is leaving BSS'.  
: 'tester' (AA:BB:CC:DD:FF:00) wlan0vap1, SSID 'test\_enterprise\_SSID', RSSI -47, 'Sending station is leaving BSS'  
SSID WPA-enterprise Response Identify ( "tester" ) , , Failure Radius . DeAssoc 'Sending station is leaving BSS'  
: 'victoria.samsonova' (RADIUS-Reject) (30:5A:3A:D9:DB:01) wlan0, SSID 'Eltex-Local', RSSI -55, 'STA was forced deauthenticated'  
-, WPA-enterprise, , .  
: AA:BB:CC:DD:FF:00() wlan0, SSID 'test\_SSID', RSSI -52, 'STA was forced deauthenticated' ( 1.9.0 )  
1.9.0 WPA-personal.  
: AA:BB:CC:DD:FF:00() wlan1, SSID 'test\_SSID', RSSI -80, 'Incorrect password' ( 1.10.0 )  
WPA-personal - .  
: AA:BB:CC:DD:FF:00() wlan1, SSID 'test\_SSID', RSSI -80, 'Disconnected by minimal signal level'  
minimal signal, - .

### OID : 1.3.6.1.4.1.35265.1.60.1.1.1.4

: AA:BB:CC:DD:FF:00 wlan0, SSID 'test\_SSID', RSSI -85, 'Disconnected by minimal signal level'  
, minimal signal, - .  
: AA:BB:CC:DD:FF:00 wlan1, SSID 'test\_SSID', RSSI -82, 'Sending station is leaving BSS'  
wifi . , ( - ). . , 2-4 dbm(--TransmitPower). .  
: AA:BB:CC:DD:FF:00 wlan0, SSID 'test\_SSID', RSSI -74, 'Sending station inactivity'  
,

```

: AA:BB:CC:DD:FF:00 wlan1, SSID 'test_SSID', RSSI -54, 'Restart hostapd'
, hostapd. - . . .:
• . hostapd . , web-,
• SSID - Radio- . . . , " SSID "
1.9.0 c hostapd.

: 'tester' (AA:BB:CC:DD:FF:00) wlan0vap1, SSID 'test_enterprise_SSID', Domain 'enterprise.test.root', RSSI -60, 'STA was forced deauthenticated'
Wi-Fi , WPA-enterprise, EMS.

: AA:BB:CC:DD:FF:00 wlan0vap3, SSID 'test_SSID', RSSI -73, 'Class 3 frame received from non-associated station'
, 'deauth' . . . , deauth 'frame received from non-associated station'.

: AA:BB:CC:DD:FF:00 wlan0, SSID 'test_SSID', RSSI -55, 'disconnect before redirect'
( 1.10.0 )

: AA:BB:CC:DD:FF:00 wlan0, SSID 'test_SSID', RSSI -55, 'Force deauthed through cportal'
( 1.10.0 )
apb. , apb.

: 'tester' (AA:BB:CC:DD:FF:00) wlan0vap1, SSID 'test_enterprise_SSID', Domain 'enterprise.test.root', RSSI -68, 'Unspecified'
"Unspecified". .

```

## **OID : 1.3.6.1.4.1.35265.1.60.1.1.1.10**

```

: AA:BB:CC:DD:FF:00 wlan0, SSID 'Eltex-Local', RSSI -72
: 'tester' (AA:BB:CC:DD:FF:00) wlan0vap4, SSID 'Eltex-Local', Domain 'enterprise.test.root', RSSI -60
WPA-enterprise ( LogOff). WPA-enterprise ( « » « Sending station is leaving BSS»

```

## **OID : 1.3.6.1.4.1.35265.1.60.1.1.1.11**

```

( 1.9.0 )
: '79234567890' (AA:BB:CC:DD:FF:00) Captive Portal wlan0, SSID 'test_SSID', Domain 'guest.test.root'
WEB .

```

## **OID : 1.3.6.1.4.1.35265.1.60.1.1.1.12**

: Client with aa:bb:cc:dd:ff:00 was deleted from AP channel wlan0, SSID Eltex-Guest, domain hotspot.root, RSSI -49, 'STA is exists at (re-) association' by AP

, / .

: Client with aa:bb:cc:dd:ff:00 was deleted from AP channel wlan0, SSID Eltex-Guest, domain hotspot.root, RSSI -49, 'Sending station is leaving (or has left) BSS' by AP

- . . . .
- . . , . .
- . . , . .

## **OID : 1.3.6.1.4.1.35265.1.60.1.1.1.13**

( 1.10.0 )

, WPA-enterprise . , - ( .. ), . . .