



# v1.14\_keepalived\_1.3.6



 **keepalived 1.3.6**  
 , 1.2.15 , 1.3.6

keepalived open source , (high availability) (load-balancing). VRRP, Linux Vitrual Server (IPVS). Keepalived Eltex , , GitHub (<http://github.com/acassen/keepalived>) .

Keepalived SoftWLC, VRRP.

keepalived Ubuntu 14.04 Wi-Fi .

```
root@master:/# dpkg -i keepalived_1.3.6-eltexu14_amd64.deb
```

root

```
/
:
service keepalived start
```

```
:
keepalived start/running, process 2471
```

```
:
root@master:/# service keepalived stop
```

```
:
keepalived stop/waiting
```

:

```
root@master:/# service keepalived status
```

:

```
keepalived start/running, process 2809
```

#### keepalived

| /etc/keepalived/keepalived.conf |                            |
|---------------------------------|----------------------------|
| /etc/keepalived/check_ping.sh   | EMS                        |
| /etc/keepalived/keep_notify.sh  | , ( MASTER, BACKUP, FAULT) |
| /etc/sysconfig/keepalived       | keepalived                 |
| /etc/keepalived/mongo_switch.js | replicaSet MongoDB , VRRP  |

## /etc/keepalived/keepalived.conf

```
! Configuration File for keepalived

global_defs {
    notification_email {
        admin@example.org
    }
    notification_email_from softwlc@example.org
    smtp_server mail.example.org
    smtp_connect_timeout 30
    router_id swlc1
    enable_traps
}

vrrp_script check_network {
    script "/etc/keepalived/check_ping.sh"
    interval 5
    weight 50
    fall 3
    rise 3
    init_fail
    user root
}

vrrp_instance VI_SWLC {
    state BACKUP
    interface eth0
    virtual_router_id 1
    track_script {
        check_network
    }
    track_interface {
        eth0 weight 50
    }
    priority 150
    advert_int 1
    nopreempt
    authentication {
        auth_type PASS
        auth_pass eltex
    }
    virtual_ipaddress {
        <virtual_ip> dev eth0 label eth0:1
    }

    notify_master "/etc/keepalived/keep_notify.sh master"
    notify_backup "/etc/keepalived/keep_notify.sh backup"
    notify_fault "/etc/keepalived/keep_notify.sh fault"

    unicast_peer {
        <ip_server1>
    }
}
```

:global\_defs, vrrp\_script, vrrp\_instance. , , VRRP.

-

:

## /etc/keepalived/check\_ping.sh

```
#!/bin/bash

# host to ping
# there - default gw
HOST=<default_gw_ip>
# -q quiet
# -c nb of pings to perform
ping -q -c5 $HOST > /dev/null

# $? var keeping result of execution
# previous command
if [ $? -eq 0 ]
then
    echo `date +%T %F` ` "OK gw reachable"
    EXIT_CODE=0
else
    echo `date +%T %F` ` "ERROR gw unreachble!"
    EXIT_CODE=1
fi

exit $EXIT_CODE
```

. , , SoftWLC .

keep\_notify.sh

## /etc/keepalived/keep\_notify.sh

```
#!/bin/bash

MYSQL_USER=""
MYSQL_PASSWORD=""

mongo_set_role() {
    local role="$1"
    if [[ "$(which mongo)" ]]; then
        mongo --quiet --eval "var role=\"$role\" admin /etc/keepalived/mongo_switch.js
        # Uncomment if using mongodb auth
        #mongo -u<username> -p<password> --quiet --eval "var role=\"$role\" admin /etc/keepalived/mongo_switch.
js
        fi
    }

if ! lockfile-create --use-pid -r 5 /tmp/keep.mode.lock; then
    echo "Unable to lock"
    echo "Unable to lock" > /tmp/keep.mode.lock.fail
    exit 0
fi

case "$1" in
    master)
        #   ems_reload_all
        echo "MASTER" > /tmp/keep.mode

        mongo_set_role master
        service eltex-ems restart
        service tomcat7 restart
        service eltex-ngw restart

        #   MySQL      -   ,
        #   heartbeat
        mysql -u$MYSQL_USER -p$MYSQL_PASSWORD -e "stop slave"
        mysql -u$MYSQL_USER -p$MYSQL_PASSWORD -e "start slave"
        ;;
    backup)
        echo "BACKUP" > /tmp/keep.mode
        mongo_set_role slave
        service mongod restart
        service eltex-ems stop
        service tomcat7 stop
        service eltex-ngw stop
        mysql -u$MYSQL_USER -p$MYSQL_PASSWORD -e "stop slave"
        mysql -u$MYSQL_USER -p$MYSQL_PASSWORD -e "start slave"
        ;;
    fault)
        echo "FAULT" > /tmp/keep.mode
        mongo_set_role slave
        service mongod restart
        ;;
    *)
        echo "Usage: $0 {master|backup|fault}"
        exit 1
esac

lockfile-remove /tmp/keep.mode.lock;

exit 0
```

replicaSet MongoDB.

## /etc/keepalived/mongo\_switch.js

```
//
var role;

if (role != 'master' && role != 'slave') {
    throw "Role must be either master or slave";
}

var thisIsMaster = (role == 'master');
var status = rs.isMaster();
var thisHost = status.me;

print("Primary: " + status.ismaster + "; applying configuration ...");
var cfg = rs.conf();
for (var i = 0; i < cfg.members.length; i++) {
    var member = cfg.members[i];
    var self = (member.host == thisHost);
    if (self ^ thisIsMaster) {
        // slave
        member.priority = 1;
        member.votes = 0;

        print(member.host + ": secondary");
    } else {
        // master
        member.priority = 2;
        member.votes = 1;

        print(member.host + ": primary");
    }
}

var result = rs.reconfig(cfg, { force: !status.ismaster });
if (result.ok == 1) {
    print("Reconfiguration done");
} else {
    print(result);
}
```

## keepalived

etc

```
keepalived /var/log/syslog. , keepalived , -. rsyslog:
```

```
nano -w /etc/rsyslog.d/10-keepalived.conf
if $programname contains 'Keepalived' then /var/log/keepalived.log
if $programname contains 'Keepalived' then ~
```

rsyslog :

```
root@swlc01-server:/# service rsyslog restart
```

```
keepalived - /var/log/keepalived.log /var/log/syslog.
```