

# v1.14\_NBI

- 
- /
- 
- - /etc/eltex-radius-nbi/radius\_nbi\_config.txt
- hikari cp
- 

SoftWLC, SOAP. : , , PCRF OSS/BSS. TLS .

eltex-axis, eltex-radius-nbi ( ).

/

tomcat ( 7 ), / .

## /etc/eltex-radius-nbi/radius\_nbi\_config.txt

SoftWLC.

- MySQL. ( ELTEX\_PORTAL, !), radius:

```
# DB radius(alias=radius)
radius.jdbc.driver=org.gjt.mm.mysql.Driver
radius.jdbc.dbUrl=jdbc:mysql://localhost/radius?
zeroDateTimeBehavior=convertToNull&useUnicode=true&characterEncoding=utf8&relaxAutoCommit=true&connectTimeout=5000
radius.jdbc.username=javauser
radius.jdbc.password=javapassword
radius.jdbc.maxPoolSize=48
radius.jdbc.inUse=yes
```

- northbound EMS, eltex-ems:

```
# ems-northbound
ems.nbi.host=127.0.0.1
ems.nbi.port=8080
ems.nbi.path=northbound
ems.nbi.protocol=http
```

- eltex-auth-service ssh, NAS .

```
# eltex_auth_service
auth.port=22
auth.host=127.0.0.1
auth.username=username
auth.password=password
```

- eltex-radius ssh, NAS.

```
# freeradius-domain-1
freeradius-domain-1.port=22
freeradius-domain-1.host=192.168.0.1
freeradius-domain-1.username=username
freeradius-domain-1.password=password
```

- Tomcat, . TLS .

```
# tomcat url
tomcat.host=127.0.0.1
tomcat.port=8080
```

- TLS. , .

```
# tomcat url
tomcat.host=127.0.0.1
tomcat.port=8080
```

- **PCRF:**

```
# pcrf stuff
pcrf.enabled=true
pcrf.url=http://localhost:7070
pcrf.username=admin
pcrf.password=password
```

- MongoDB **pcrf:**

```
# pcrf mongodb connector
pcrf.mongodb.enabled=true
pcrf.mongodb.uri=mongodb://localhost:27017/pcrf
```

- MongoDB **wifi-customer-cab:**

```
# wifi-customer-cab mongodb connector
wificab.mongodb.enabled=true
wificab.mongodb.uri=mongodb://localhost:27017/wifi-customer-cab
```

- SORM2 (Mongo)

```
# Eltex.SORM2.replicator MongoDB 'sorm2' connect
sorm2.mongodb.enabled=false
sorm2.mongodb.uri=mongodb://localhost:27017/sorm2
```

- SORM2

```
# Eltex.SORM2.replicator host to use API
sorm2.enabled=false
sorm2.url=http://localhost:7071
sorm2.username=admin
sorm2.password=password
```

- -3. Wi-Fi, Wi-Fi.

```
#It enables records export to SORM3 while editing wifi users
sorm3.enabled=false
```

- . 90000.

```
# wifi-customer-cab request settings
wificab.timeout=90000
```

hikari cp

eltex-radius-nbi mysql hikari cp, , /etc/eltex-radius-nbi/hikari.properties

```
;
connectionTimeout=15000
, , connectionTimeout;
validationTimeout=3000
, . 10000(10 ), 600000 (600 );
idleTimeout=30000
, hikari cp .
minimumIdle=1
```

eltex-radius-nbi. <http://localhost:8080/eltex-radius-nbi/asciidoc/>

WSDL <http://localhost:8080/axis2/services/RadiusNbiService?wsdl>

(localhost ip nbi)