/domain/<DOMAIN>/sip/ldap

- check
- clean
- domain
- info
- set
- user

LDAP.
LDAP- , .
LDAP-, SSW (..).
.

LDAP . DS.

<DOMAIN> - .

1 LDAP.

1 - LDAP

access.login	cn=admin,dc=ecss	,
access.passw	admin	
access.path	ou=sip1,dc=ecss	, /
alive_timeout	10000	LDAP- (,)
attr.domain	dc	,
attr.login	cn	,
attr.passw	description	,
attr.phone	telephoneNumber	,
enable	false	(true) (false) LDAP-
ip	localhost	IP- LDAP-
port	389	LDAP-

check

LDAP (,). LDAP-. .

:

domain/<DOMAIN>/sip/ldap/check

:

check

:

.

:

```
./check
Executed on the sip1@ecss1
--------------------------------------
|    Node    |         Check         |
|------------+-----------------------|
| sip1@ecss1 | {connected,<0.625.0>} |
--------------------------------------
```

clean

LDAP.

:

/domain/<DOMAIN>/sip/ldap/clean

:

clean [<KEY>]

:

<KEY> - , . . , . 1.

:

```
./clean ip
Property ip values successfully restored
```

domain

SIP.

:

domain/<DOMAIN>/sip/ldap/domain

:

domain <ACT>

:

<ACT> - , :

- list - ;
- remove - <DOMAIN> .
- --force - .

:

:

```
./domain list
Executed on the sip1@ecss1
["192.168.1.2","192.168.1.4","192.168.18.18","92.125.153.132"]

[exec at: 26.02.2015 10:31:08, exec time: 79ms, nodes: sip1@ecss1]
```

info

LDAP.

:

domain/<DOMAIN>/sip/ldap/info

:

info [<KEY>]

:

<KEY> – , , LDAP. 1.

:

```
./info
-----------------------------------------------
|  Property   |  Domain   |      Value       |
|-------------+-----------+------------------|
|access.login |test.domain|"cn=admin,dc=ecss"|
|access.passw |test.domain|"admin"           |
|access.path  |test.domain|"ou=sip1,dc=ecss" |
|alive_timeout|test.domain|10000             |
|attr.domain  |test.domain|"dc"              |
|attr.login   |test.domain|"cn"              |
|attr.passw   |test.domain|"description"     |
|attr.phone   |test.domain|"telephoneNumber" |
|enable       |test.domain|true              |
|ip           |test.domain|"localhost"       |
|port         |test.domain|"389"             |
-----------------------------------------------
```

set

LDAP.

:

domain/<DOMAIN>/sip/ldap/set

:

set <KEY> <VALUE>

:

<KEY> – . 1.
<VALUE> - .

:

IP- LDAP- 192.168.23.23:

```
./set ip 192.168.18.111
Property "ip" successfully changed from:
"localhost"
   to
"192.168.18.111".
```

LDAP- 389:

```
./set port 389
Property "port" successfully changed from:
"389"
   to
"389".
```

/ «pa_sip»:

```
./set access.path ou=sip1, dc=ecss
Property "'access.path'" successfully changed from:
"ou=sip1,dc=ecss"
   to
"ou=sip1, dc=ecss".
```

user

SIP- LDAP.

:

domain/<DOMAIN>/sip/ldap/user

:

user list <DOMAIN>
user remove <DOMAIN> [--force]
user test <DOMAIN> <USER> <LOGIN> <PASSWORD>

:

- user list – SIP- ();
- user remove – () ;
- user test – ;

<DOMAIN> - ;
[--force] - ;
<PHONE> - ;
<DOMAIN> + <PHONE> <USER> + <PASSWORD>.

. .
. .

<USER> - ;
<PASSWORD> - .

:

```
./users list eltex.local
```