

SIP- :

```
/domain/<DOMAIN>/sip/user/declare <ROUTING_CONTEXT> <GROUP> <INTERFACE> [<ALIAS> [<QOP_AUTH> [<LOGIN> [<PASSWORD>]]]]
```

```
<DOMAIN> - ;<ROUTING_CONTEXT> - ;  
<GROUP> - , . ;  
<INTERFACE> - , :username@host, username - ; host - SIP- . {a-b} {a,b}, a,b - .  
, 1111@eltex.local, 1112@eltex.local, 1113@eltex.local 111{1-3}@eltex.local 111{1,2,3}@eltex.local {1111,1112,1113}@eltex.local. SIP- ;  
<ALIAS> - , "none" SIP, SIP="text.users.name@some.sip.area", ECSS-10 , . SIP- <ALIAS> - () ;  
<QOP_AUTH> - QOP-( ). :
```

- no_qop_authentication - QOP-;
 - qop_authentication - QOP-;

<LOGIN> - . . / , LDAP-:

- login_as_number - ;
 - none - ;
 - common_login <LOGIN> - <LOGIN> .

<PASSWORD> - . , <LOGIN> "none".

- auto_generation - . . . "user info" "user authentication";
 - () - .

, , IP- ("trusted-ip"):

```
domain/test.domain/sip/user/declare local smg 401@test.domain none no_qop_authentication
```