

# MYSQL

## MySQL

MySQL - . :

- OPTIMIZE TABLE:

```
% cdr  
OPTIMIZE TABLE cdr;  
% tolltickets  
OPTIMIZE TABLE tolltickets;
```

```
OPTIMIZE TABLE      (, VARCHAR, BLOB TEXT). , INSERT . , , OPTIMIZE TABLE.
```

```
: MySQL (, ) /var/lib/mysql. , . , . ( tolltickets 50 3), ( ).  
slave (, IP MySQL). , IP master, slave).
```

- dump , truncate table. .

```
, dump ( dump /var/lib/mysql-files), MySQL .
```

1:

, , :

```
% tolltickets  
SELECT * FROM tolltickets INTO OUTFILE '/var/lib/mysql-files/tolttickets.dump' CHARACTER SET utf8 FIELDS  
TERMINATED BY ',' OPTIONALLY ENCLOSED BY '\"' LINES TERMINATED BY '\n';  
% tolltickets  
TRUNCATE TABLE tolltickets;  
%  
LOAD DATA INFILE "/var/lib/mysql-files/tolttickets.dump" IGNORE INTO TABLE tolltickets CHARACTER SET  
utf8 FIELDS TERMINATED BY ',' OPTIONALLY ENCLOSED BY '\"' LINES TERMINATED BY '\n';
```

- , TRUNCATE TABLE, ; LOAD DATA INFILE - ;
- SELECT TRUNCATE , .

2 ( MySQL ):

. . tolttickets. IP MySQL ecss1:

1. (ecss1, ecss2):

```
show slave status \G;
```

Seconds\_Behind\_Master = 0, Slave\_IO\_Running: Yes, Slave\_SQL\_Running: Yes.  
2. (ecss1, ecss2)

```
stop slave;
```

3. backup ecss2 (ecss2):

```
% tolttickets  
SELECT * FROM tolttickets INTO OUTFILE '/var/lib/mysql-files/tolttickets.dump' CHARACTER SET utf8  
FIELDS TERMINATED BY ',' OPTIONALLY ENCLOSED BY '\"' LINES TERMINATED BY '\n';
```

4. ( , ), SELECT ... INTO OUTFILE WHERE.  
4. master- ecss2 (ecss2):

```
show master status \G;
***** 1. row *****
      File: server-mysql-bin.002123
      Position: 532
Binlog_Do_DB:
Binlog_Ignore_DB: information_schema,mysql,performance_schema
Executed_Gtid_Set:
1 row in set (0.00 sec)
```

File, Position. .

5. tolltickets ecss2 (ecss2):

```
TRUNCATE TABLE tolltickets;
```

6. (ecss2):

```
LOAD DATA INFILE "/var/lib/mysql-files/tolltickets.dump" IGNORE INTO TABLE tolltickets CHARACTER SET utf8 FIELDS TERMINATED BY ',' OPTIONALLY ENCLOSED BY '\"' LINES TERMINATED BY '\n';
```

ecss2 tolltickets dump. slave ecss2, , slave tolltickets.

7. slave ecss2 (ecss2):

```
start slave;
```

8. , ecss2 ecss1 (ecss2):

```
show slave status \G;
```

, Seconds\_Behind\_Master .

9. IP MySQL ecss1 ecss2 (ecss2).  
ecss2 keepalived (/etc/keepalived/keepalived.conf) "vrrp\_instance VI53" ( ecss2 50, 101), keepalived.

```
sudo systemctl restart keepalived
```

10. , ecss2 (ecss2).

, IP , 1 , ecss1 .

11. slave ecss2 (ecss2):

```
show slave status \G;
```

, Seconds\_Behind\_Master .

12. slave ecss2 (ecss2):

```
stop slave;
```

13. tolltickets ecss1 (ecss1):

```
TRUNCATE TABLE tolltickets;
```

14. slave ecss1 , 5 (ecss1):

```
CHANGE MASTER TO MASTER_LOG_FILE='server-mysql-bin.002123', MASTER_LOG_POS=532;
```

15. slave ecss1 (ecss1):

```
start slave;
```

16. , ecss1 ecss2 (ecss1):

```
show slave status \G;
```

17. master ecss1 (ecss1):

```
show master status \G;
*****
      1. row ****
      File: server-mysql-bin.000087
      Position: 142612
      Binlog_Do_DB:
      Binlog_Ignore_DB: information_schema,mysql,performance_schema
      Executed_Gtid_Set:
      1 row in set (0.00 sec)
```

File, Position. .

18. slave ecss2 , 18 (ecss2):

```
CHANGE MASTER TO MASTER_LOG_FILE='server-mysql-bin.000087', MASTER_LOG_POS=142612;
```

19. slave ecss2:

```
start slave;
```

20. , (ecss1, ecss2):

```
show slave status \G;
```

Seconds\_Behind\_Master = 0, Slave\_IO\_Running: Yes, Slave\_SQL\_Running: Yes.  
21. keepalived ecss2 (ecss2).



MySQL (/var/lib/mysql) /tmp. , /tmp .