

Hc_calendar_timetable -

- [Hc_calendar_timetable_show](#)
- [Hc_calendar_timetable_set](#)
- [Hc_calendar_timetable_remove](#)

Hc_calendar_timetable_show

CoCon:

/domain/<DOMAIN>/calendar/timetable/show

URL

http://host:port/commands/calendar_timetable_show

HTTP-:

200 - ;
404 - .

XML-

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:include schemaLocation="error.xsd"/>
  <!-- timetableType -->
  <xs:complexType name="timetableType">
    <xs:attribute name="name" type="xs:string" use="required"/>
    <xs:attribute name="value" type="xs:string" use="required"/>
  </xs:complexType>
  <!-- resultType-->
  <xs:complexType name="resultType">
    <xs:sequence>
      <xs:element name="timetable" type="timetableType" minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
  <!-- in-->
  <xs:element name="in">
    <xs:complexType>
      <xs:all>
        <xs:element name="request">
          <xs:complexType>
            <xs:attribute name="domain" type="xs:string" use="optional"/>
            <xs:attribute name="timetable" type="xs:string" use="optional"/>
          </xs:complexType>
        </xs:element>
      </xs:all>
    </xs:complexType>
  </xs:element>
  <!-- out-->
  <xs:element name="out">
    <xs:complexType>
      <xs:choice>
        <xs:element name="error" type="errorType"/>
        <!--Positive case-->
        <xs:element name="result" type="resultType"/>
      </xs:choice>
    </xs:complexType>
  </xs:element>
</xs:schema>
```

:
http://192.168.1.21:9999/commands/calendar_timetable_show

```
<?xml version="1.0"?>
<in
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="
hc_calendar_timetable_show.xsd">
  <request domain="biysk.local"/>
</in>
```

:

```
<?xml version="1.0"?>
<out
  xmlns:xs="http://www.w3.org/2001/XMLSchema-instance" xs:noNamespaceSchemaLocation="
hc_calendar_timetable_show.xsd">
  <result>
    <timetable name="tt4" value="{\"name\":\"tt4\", \"filters\": [{\"date\":\"1 2 3 4 5\", \"from\":\"9:0\", \"to\":\"18:0\"}], \"
properties\": []}\"/>
  </result>
</out>
```

Hc_calendar_timetable_set

'''

CoCon:

```
/domain/<DOMAIN>/calendar/timetable/add-interval
/domain/<DOMAIN>/calendar/timetable/remove-interval
```

URL

http://host:port/commands/calendar_timetable_set

HTTP-:

```
200 - ;
404 - .
```

XML-

```

<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema">
<!-- <error> -->
  <xs:complexType name="errorType">
    <xs:attribute name="name" type="xs:string" use="optional" />
    <xs:attribute name="reason" type="xs:string" use="optional" />
    <!-- entity="[nonempty_string()]" -->
  </xs:complexType>
  <!-- timetableType -->
  <xs:complexType name="timetableType">
    <xs:attribute name="name" type="xs:string" use="required"/>
    <xs:attribute name="value" type="xs:string" use="required"/>
  </xs:complexType>
  <!-- requestType-->
  <xs:complexType name="requestType">
    <xs:sequence>
      <xs:element name="timetable" type="timetableType" minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute name="domain" type="xs:string" use="optional"/>
  </xs:complexType>
  <!-- resultType-->
  <xs:complexType name="resultType">
    <xs:choice>
      <xs:sequence>
        <xs:element name="error" type="errorType"/>
      </xs:sequence>
      <!--Positive case-->
      <xs:element name="ok"/>
    </xs:choice>
  </xs:complexType>
  <!-- in-->
  <xs:element name="in">
    <xs:complexType>
      <xs:all>
        <xs:element name="request" type="requestType"/>
      </xs:all>
    </xs:complexType>
  </xs:element>
  <!-- out-->
  <xs:element name="out">
    <xs:complexType>
      <xs:all>
        <xs:element name="result" type="resultType"/>
      </xs:all>
    </xs:complexType>
  </xs:element>
</xs:schema>

```

:

http://192.168.1.21:9999/commands/calendar_timetable_set

```

<?xml version="1.0"?>
<in
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="
hc_calendar_timetable_set.xsd">
  <request domain="biysk.local">
    <timetable name="tt4" value="{\"name\":\"tt4\",\"filters\": [{\"date\":\"1 2 3 4 5\", \"from\":\"9:0\", \"to\":\"18:0\"}], \"
properties\":[]}\""/>
  </request>
</in>

```

:

```
<?xml version="1.0"?>
<out
  xmlns:xs="http://www.w3.org/2001/XMLSchema-instance" xs:noNamespaceSchemaLocation="
hc_calendar_timetable_set.xsd">
  <result>
    <ok/>
  </result>
</out>
```

Hc_calendar_timetable_remove

CoCon:

domain/<DOMAIN>/calendar/timetable/remove

URL

http://host:port/commands/calendar_timetable_remove

HTTP-:

200 - ;
404 - .

XML-

```

<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema">
<!-- <error> -->
  <xs:complexType name="errorType">
    <xs:attribute name="name" type="xs:string" use="optional" />
    <xs:attribute name="reason" type="xs:string" use="optional" />
    <!-- entity="[nonempty_string()]" -->
  </xs:complexType>
<!-- timetableType -->
<xs:complexType name="timetableType">
  <xs:attribute name="name" type="xs:string" use="required"/>
</xs:complexType>
<!-- requestType-->
<xs:complexType name="requestType">
  <xs:sequence>
    <xs:element name="timetable" type="timetableType" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="domain" type="xs:string" use="optional"/>
</xs:complexType>
<!-- resultType-->
<xs:complexType name="resultType">
  <xs:choice>
    <xs:sequence>
      <xs:element name="error" type="errorType"/>
    </xs:sequence>
    <!--Positive case-->
    <xs:element name="ok"/>
  </xs:choice>
</xs:complexType>
<!-- in-->
<xs:element name="in">
  <xs:complexType>
    <xs:all>
      <xs:element name="request" type="requestType"/>
    </xs:all>
  </xs:complexType>
</xs:element>
<!-- out-->
<xs:element name="out">
  <xs:complexType>
    <xs:all>
      <xs:element name="result" type="resultType"/>
    </xs:all>
  </xs:complexType>
</xs:element>
</xs:schema>

```

:
http://192.168.1.21:9999/commands/calendar_timetable_remove

```

<?xml version="1.0"?>
<in
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="
hc_calendar_timetable_remove.xsd">
  <request domain="biysk.local">
    <timetable name="tt4"/>
  </request>
</in>

```

:

```
<?xml version="1.0"?>
<out
  xmlns:xs="http://www.w3.org/2001/XMLSchema-instance" xs:noNamespaceSchemaLocation="
hc_calendar_timetable_remove.xsd">
  <result>
    <ok/>
  </result>
</out>
```